

FIRE ISOLATOR

Datasheet FireBlanket FI-BLECON0806

Product description

The T-ISS FireBlanket can be used for normal, combustion-engined and EV car fires. It can be deployed in parking garages, parking lots, shopping malls, onboard ferries, etc. The blanket can be used for all car sizes from a small city car up to large SUV models. Due to depriving the oxygen inlet, the car fire will be isolated. The fire will not spread and will avoid collateral damage, also the smoke spread will stop and gives fire crews easier access to the vehicle. It has a smooth working temperature of 800°C. The Fire Blanket FI-BLECON0806 is easy to deploy by 2 people.

Our blankets have no expiration date, they have a shelflife of 25 year+ when properly stored.

Pictures



Dimensions & Specifications

Art. No: FI-BLECON0806 FireBlanket ≈
 Size: 800 x 600 cm *
 Weight: 29 kg
 Material: Silica grade, eco friendly
 Temperature: + 800 °C tested
 Tests: ASTM D6413, ISO 13501-1

Item	Specification	
Weave	8HS Stain	
Thickness (mm)	0.7±0.07	
Width (mm)	6000 ±5%	
Length (mm)	8000 ±5%	
Weight (g/m ²)	600± ³⁰ / ₂₀	
Count	Wrap (pick/cm)	18±1
	Weft (pick/cm)	14±1
Tensile Strength	Wrap (N/25x100mm)	1000
	Weft (N/25x100mm)	800
SiO ₂ Content (%)	≥70	
Temperature(°C)	800	

Pictures



- Supplied in sturdy bag
- Cabinet available
- Big loops for easy handling of the blanket
- Tan/Off white colour
- Suitable from small cars to large Pickups

* The blanket has +/- 5% tolerance for its width and length. The width and length can be affected by environmental temperature and moisture level. Some of the cloth is included in the folded margin.

Pictures



Visit our website:

FIREISOLATOR.COM

© COPYRIGHT T-ISS B.V. - All rights reserved

T-ISS
Safety Suppliers

Global