

FIRE ISOLATOR

Datasheet FireBlanket Ultimate FI-BL0906

Product description

The T-ISS FireBlanket Ultimate FI-BL0906 can be used for normal, combustion-engined and EV car fires. It can be deployed in parking garages, parking lots, shopping malls, onboard ferries, etc. The blanket can be used for all car sizes from a small city car up to large SUV models.

Due to depriving the oxygen inlet, the car fire will be isolated. The fire will not spread and will avoid collateral damage, also the smoke spread will stop and gives fire crews easier access to the vehicle.

The FireBlanket is reusable and can be cleaned. It can stand peak temperatures of 1600 °C, and can withstand 1200 °C for more than 50 hours. The FireBlanket Ultimate FI-BL0906 is easy to deploy by 2 people.

Pictures



Dimensions & Specifications

Art. no: FI-BL0906

Dimensions: 9 x 6 m*

Weight: 37 kg

Material: 96,6% Highest quality Silica, eco friendly

Temperature

resistance: + 1600 °C peak

Classification: DIN EN 13501-1 classified with A1
certificate by KIWA/ MPA, ASTM D6413
classified by HPL Engineering

HS code: 70199000

Usage: reusable

Also available in 2x2, 3x3, 5x5, 6x6, 7x7 and other custom-made sizes.

Pictures



- Supplied in sturdy smartbag
- Cabinet available
- Big coloured loops for easy handling of the blanket
- Trolley and backpack available
- Suitable from small cars to large Pickups
- No expiration date, shelflife of 25 year+ if properly stored

* The blanket has a tolerance of +/- 5% in width and length, which can be affected by temperature and moisture.

Pictures



Visit our website:

FIREISOLATOR.COM

© COPYRIGHT T-ISS B.V. - All rights reserved

T-ISS
Safety Suppliers

Global